



K1-610

WATER-BASED CONCRETE & MASONRY PRIMER

K1-610 is a styrene-acrylic coating specifically engineered for interior and exterior. It's perfect for sealing and conditioning porous masonry surfaces.

Details

- Sealer and adheres to concrete, brick and plaster.
- Conditions porous masonry surfaces.
- Economical.

Recommend Uses

- Concrete, Concrete Block, Brick, Stucco, Fiber Cement Siding, Mortar, Exterior Wall Cladding.

Applications

Surface Preparation

- All new masonry, concrete, cement or block must be cured for 30 days at recommended.
- Remove all loose paint and defective paint if possible, oil, fluid, moss or other substances on the surface. In severe cases, wash the surface with water, make sure the surface is completely dried and clean. All holes cracks must be properly patched.

Application Details

- Product must be completely agitated (mechanically or manually) before use.
- Intermix containers of same product to ensure color and seen uniformity.

- Dilution is prohibited! Minimum of one coat is required. Second coat is strongly recommended for the best result.

Technical Data

Property	Value
Tools	Nylon / Polyester Brush, Sponge Paint Roller, Sprayer
Drying Time	Touch Dry 30-60 Minutes, Recoat 1-2 Hours (at 25°C)
Coverage	13 m ² Coverage per Gallon
Thickness	Dry 50 µm
Available Sheen	Flat
Density	1 kg/L
Viscosity	<500 m.Pas at 25°C
Solid Content	--
Available Size	1 Gallon, 5 Gallon
Thinner	--
Shelf Life	36 months unopened condition
Color	Milky White

Drying and recoat times are temperature, humidity, and film thickness dependent.

Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and film thickness.

These figures are only intended as a guide and should not be used in preparing specifications.

Storage

Product should be store in the dry and cool area, please avoid direct sunlight contact to prevent deterioration. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

After container is opened, use the product immediately and prevent long-term storage.

Cautions and Safety

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F.
- KEEP OUT REACH OF CHILDREN – DO NOT TAKE INTERNALLY.
- When spraying. Do not breathe spray, wear suitable respiratory protective equipment.

- Avoid direct contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek for the medical advice.
- After contact with skin, wash with soap and water.
- Safety Data Sheet (SDS) is available on www.kingcatpaint.com.tw.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Yulung Paint. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Yulung Paint representatives or visit www.kingcatpaint.com.tw to obtain the most current version of the Technical Data Sheet and / or a Safety Data Sheet.