



K1-176 Series

## WATER-BASED ELASTIC WATERPROOF PAINT

K1-176 is the solution for building owners looking for roof coating that provides standard ponding water resistant.

### Details

- Ponding water resistant.
- Excellent flow and leveling.
- Excellent adhesion to concrete surface.
- Economical.

### Recommend Uses

- Roof and exterior wall.
- Concrete block, Brick Stucco, Cement, Concrete Surface, Cement Composition Siding/Panels, Asbestos and Wood.

### Applications

#### Surface Preparation

- All new masonry, concrete, cement or block must be cured for 30 days at recommended.
- Remove all loose paint and defective paint if possible, oil, fluid, moss or other substances on the surface. In severe cases, wash the surface with water, make sure the surface is completely dried and clean. All holes cracks must be properly patched.

## Application Details

- Product must be completely agitated (mechanically or manually) before use.
- Intermix containers of same product to ensure color and seen uniformity.
- Dilution is no needed.
- Priming and application of two coats at the recommended film thickness / practical coverage when application to new surfaces.
- Priming may not be needed when application on previously painted. Consult with your representative before application.

## Technical Data

| Property        | Value   |
|-----------------|---|
| Tools           | Nylon / Polyester Brush, Sponge Paint Roller, Sprayer |
| Drying Time     | Touch Dry 1-2 Hours, Recoat 6-8 Hours (at 25°C)       |
| Coverage        | 12.5 m <sup>2</sup> Coverage per Gallon               |
| Thickness       | Wet 500 µm, Dry 200 µm                                |
| Available Sheen | Semi-Gloss  |
| Density         | 1.2 kg/L  |
| Viscosity       | 9,000-10,000 m.Pas at 25°C                            |
| Solid Content   | 35% ± 2%  |
| Available Size  | 5 Gallon  |
| Shelf Life      | 24 months unopened condition                          |
| Color           | Visit our website for more details                    |

Drying and recoat times are temperature, humidity, and film thickness dependent.

Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and film thickness.

**These figures are only intended as a guide and should not be used in preparing specifications.**

## Storage

Product should be store in the dry and cool area, please avoid direct sunlight contact to prevent deterioration. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

After container is opened, use the product immediately and prevent long-term storage.

## Cautions and Safety

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F.
- KEEP OUT REACH OF CHILDREN – DO NOT TAKE INTERNALLY.
- When spraying. Do not breathe spray, wear suitable respiratory protective equipment.
- Avoid direct contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek for the medical advice.
- After contact with skin, wash with soap and water.
- Safety Data Sheet (SDS) is available on [www.kingcatpaint.com.tw](http://www.kingcatpaint.com.tw).

## Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Yulung Paint. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Yulung Paint representatives or visit [www.kingcatpaint.com.tw](http://www.kingcatpaint.com.tw) to obtain the most current version of the Technical Data Sheet and / or a Safety Data Sheet.