

K1-907

WATER-BASED PENETRATING WATERPROOF PAINT

Employ the latest waterproofing technology in a range of systems applicable to porous substrates, such as concrete, brickwork, stone and mortar. K1-907 treatment can be used on any porous substrate without changing its appearance, to maintain a dry look. This white spirit-based formula penetrates deep into pores and lines them with the product, reducing the pore size so that liquid can no longer pass through the substrate, while still allowing it to breathe.

Details

- Easy to apply.
- Non-Yellowing, Alkali and UV resistant.
- Invisible, dry and natural look finish.
- Protection against damage caused by moisture intrusion.
- No more scrubbing and power washing.
- Decreases dirt adhesion and prevents moss and mildew growth.

Recommend Uses

- Concrete, Brickwork, Masonry Blocks, Natural Stones, Stucco, Traffic Bearing Surfaces.

Applications

Surface Preparation

- All new masonry, concrete, cement or block must be cured for 30 days as recommended.
- Remove all loose paint and defective paint if possible, oil, fluid, moss or other substances on the surface. In severe cases, wash the surface with water, make sure the surface is completely dried and clean. All holes cracks must be properly patched.

Application Details

- DO NOT DILUTE THIS PRODUCT.
- Product must be completely agitated (mechanically or manually) before use.
- Intermix containers of same product to ensure color and seen uniformity.
- Application of 2-3 coats at the recommended film thickness / practical coverage when application to new surfaces.

Technical Data

Property	Value
Tools	Nylon / Polyester Brush, Sponge Paint Roller, Sprayer
Drying Time	Touch Dry 5-10 Minutes, Recoat 30-60 Minutes (at 25°C)
Coverage	26 m ² Coverage per Gallon
Available Sheen	Flat
Density	1 kg/L
Viscosity	>500 m.Pas at 25°C
Available Size	1 Gallon, 5 Gallon
Thinner	--
Shelf Life	36 months unopened condition
Color	Transparent

Drying and recoat times are temperature, humidity, and film thickness dependent.

Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and film thickness.

These figures are only intended as a guide and should not be used in preparing specifications.

Storage

Product should be store in the dry and cool area, please avoid direct sunlight contact to prevent deterioration. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

After container is opened, use the product immediately and prevent long-term storage.

Cautions and Safety

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F.

- KEEP OUT REACH OF CHILDREN – DO NOT TAKE INTERNALLY.
- When spraying. Do not breathe spray, wear suitable respiratory protective equipment.
- Avoid direct contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek for the medical advice.
- After contact with skin, wash with soap and water.
- Safety Data Sheet (SDS) is available on www.kingcatpaint.com.tw.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Yulung Paint. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Yulung Paint representatives or visit www.kingcatpaint.com.tw to obtain the most current version of the Technical Data Sheet and / or a Safety Data Sheet.